



MC-31

Order No.: 0251690

PRODUCTINFOS

3-way microphone combiner,

(3 inputs/1 output), for connecting 3 microphones to e.g. one microphone input of a mixer.

- Balanced XLR connections (200 Ω)
- Frequency range: 20-20,000 Hz
- Also suitable for microphones with phantom power
- Robust metal housing with very good shielding qualities, suitable for stage applications
- Dimensions: 125 x 55 x 75 mm
- Weight: 563 g

SOUNDCHECK 07/2007

on the FGA-102, FGA-202, LC-31, MC-31 and LSP-102:

“Every musician or sound engineer should have these little helpers in their toolbox. They impress by their unobtrusiveness. Both the robust metal housing and the functionality of these transformers allow to solve many problems on stage or in the studio at a reasonable price.”

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages

The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).
If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

TECHNICAL SPECIFICATIONS

MC-31

Description	combiner
Frequency range	20-20,000 Hz
Input impedance	200 Ω
Admiss. ambient temp.	0-40 °C
Dimensions	125 x 55 x 75 mm
Weight	563 g
Inputs	3 x XLR, bal.
Outputs	1 x XLR, bal.

MC-31

EAN code	4007754197747
Net weight	0.536 kg