



TXS-606LT/2

Order No.: 1000186

PRODUCTINFOS

Multifrequency tie clip microphone transmitter,

with UHF PLL technology.

- 800 selectable UHF frequencies (672.000-691.975 MHz), can be synchronised with receivers TXS-606, TXS-626, TXS-646 or TXS-686 via ACT function
- Continuously adjustable sensitivity
- LCD for indicating group/channel, audio level and battery status
- Tie clip microphone with latchable 3.5 mm plug
- Belt clip
- Power supply via 2 x 1.5 V battery AA size (not supplied)

There are restrictions or requirements within the EU!

Please read the information regarding wireless systems in the section “IMPORTANT INFORMATION”!

SOUNDCHECK 04/2012

“The TXS-646 can receive four wireless channels at the same time - the hand-held transmitter provides a warm and powerful sound and stands its ground among the instruments ... the earband microphones allow for unobtrusive miking with both a low susceptibility to acoustic feedback and an excellent speech intelligibility ... the quad wireless system from IMG Stage Line provides a reliable operation at all times, is easy to use and impresses by a crisp sound.”

+ Clear sound

+ Very good price-performance ratio

+ Future-proof frequency range

(Test setup consisted of TXA-646 with TXS-606HT, TXS-606LT and HSE-70A/SK)

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages

The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).

Remove the rechargeable batteries or batteries if the device is not in use for a longer period of time (e.g. more than a week). This avoids possible damage through leaking batteries.

If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

Batteries and rechargeable batteries must not be disposed of with household waste. They must be disposed of in accordance with local regulations for hazardous waste.

TECHNICAL SPECIFICATIONS

TXS-606LT/2

General information

Description	pocket transmitter
Carrier frequency range	672.000-691.975 MHz
Audio frequency range	30-18,000 Hz
Channels	1
Operating time	> 8 h
Admiss. ambient temp.	0-40 °C
Specifications transmitter	
Transmitting power	10 mW
Power supply transmitter	2 x 1.5 V batt. AA size

TXS-606LT/2

Width transmitter	61 mm
Height transmitter	106 mm
Depth transmitter	27 mm
Weight transmitter	96 g
Connections transmitter	1 x 3.5 mm jack

TXS-606LT/2

EAN code	4007754276190
Net weight	0.096 kg