

Tender text

TXS-811SET

Multifrequency microphone system,

with UHF PLL technology.

- 1 hand-held microphone transmitter (cardioid polar pattern), 1 receiver, 1 plug-in power supply
- Switching diversity system
- 9 selectable UHF channels
- Volume and squelch controls
- 482 mm (19") rack installation of 2 receiver units possible with supplied mounting brackets

Licence-free in the EU.

Specifications:

General information

Description	wireless microphone system
Carrier frequency range	863-865 MHz
Audio frequency range	50-15,000 Hz
Channels	1
THD	< 1%
Dynamic range	> 100 dB
RF S/N ratio	> 90 dB
Admiss. ambient temp.	0-40 °C
Specifications transmitter	
Transmitting power	< 10 mW
Operating range	approx. 30 m
Power supply transmitter	2 x 1.5 V batt. AA size
Width transmitter	48 mm
Height transmitter	48 mm
Depth transmitter	235 mm
Weight transmitter	165 g
Specifications receiver	
Audio signal receiver	50 mV/10 kΩ (jack) 100 mV/10 kΩ (XLR, bal.)
Power supply receiver	via encl. plug-in power supply
Width receiver	200 mm
Height receiver	45 mm
Depth receiver	130 mm
Weight receiver	370 g
Connections receiver	1 x XLR, bal., 1 x 6.3 mm jack, unbal.

Brand: IMG STAGELINE

Type: TXS-811SET

Quantity: 1

Packing dimensions (W x H x L): 0.27 x 0.065 x 0.4 m

Gross weight: 1.391 kg

Net weight: 0.952 kg

Item weight (w/o accessories): 0.952 kg